



# Architectural MSD

## MSD 575 1CT/16

The high luminous efficacy and optimal lamp filling of the single ended Architectural MSD lamps create high beam intensity and excellent color rendering. While the compact arc of the lamp allows efficient beam control and high intensity. Ideal to illuminate architecture of all types at night.

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Operating and Electrical	
Cap-Base	GX9.5 [ GX9.5]	Power (Nom)	575 W
Operating Position	UNIVERSAL [ Any or Universal (U)]	Lamp Current (Nom)	7.6 A
Main Application	Studio/Disco	Ignition Supply Voltage (Min)	207 V
Life to 50% Failures (Nom)	3000 h		
System Description	-	Controls and Dimming	
		Dimmable	No
Light Technical		Mechanical and Housing	
Color Code	- [ Not Specified]	Cap-Base Information	-
Luminous Flux (Min)	38700 lm	Luminaire Design Requirements	
Luminous Flux (Nom)	43000 lm	Bulb Temperature (Max)	700 °C
Chromaticity Coordinate X (Nom)	323	Pinch Temperature (Max)	350 °C
Chromaticity Coordinate Y (Nom)	317		
Correlated Color Temperature (Nom)	6000 K	Product Data	
Luminous Efficacy (Rated) (Min)	68 lm/W	Full product code	872790091755000
Luminous Efficacy (rated) (Nom)	75 lm/W	Order product name	MSD 575 1CT/16
Color Rendering Index (Nom)	72		

# Architectural MSD

EAN/UPC - Product	8727900917550
Order code	928098805114
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	16

Material Nr. (12NC)	928098805114
Net Weight (Piece)	0.062 kg

## Dimensional drawing

D

Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSD 575	30 mm	8.0	64 mm	66 mm	65	125 mm	36 mm	35	34 mm
1CT/16		mm			mm			mm	

MSD 575

## Photometric data

